DEPARTMENT OF BUILDING & SAFETY



(2) Size, depth and reinforcement of foundation.

RESIDENTIAL ATTACHED OR DETACHED STRUCTURE SUBMITTAL REQUIREMENTS

333 North Rancho Drive, Las Vegas NV 89106-3703

Phone: (702) 229-6251 Fax: (702) 382-1240

| 1.1 | PLOT/SITE/GRADING PLANS (Two 8-1/2" x 11" minimum and 42" x 30" maximum plot plans required). | | \square (3) Post-tensioned slab foundation where required. | |
|-----|---|-----|---|--|
| | A. Legal description of plot or lot. | | \Box (4) Sections and details. | |
| | B. Property lines or boundaries with dimensions shall be clearly identified. | | □ (5) Material specifications and foundation notes. □ D. Framing Plans and Details: | |
| | C. Show all easements, right-of-ways, and street names. | | □ D. Framing Plans and Details: □ (1) Roof and floor framing plans showing location and spacing of trusses, joists and rafters, beams, | |
| | D. Show location of all proposed and existing buildings. Dimensioned setbacks and building use shall be identified. | | headers, posts, trimmers, king studs, exterior and interior bearing walls, framing hardware, connections and details. | |
| | E. Show septic tank, leach field, and well locations. | | ☐ (2) Lateral force resisting system including shear walls, rigid frames, cantilevered columns, drag struts, collectors, diaphragm, nailing schedule, hold-downs, | |
| | F. Two Soil Reports for single story remodels or additions with a 600 square foot or greater footprint. | | framing hardware and connections. | |
| 1.2 | BUILDING PLANS: (Two sets required) | | ☐ (3) Structural details depicting explicit and complete load path and shear transfer details from point of load application to vertical and lateral load resisting | |
| | A. Plans shall be complete and shall consist of architectural, structural, electrical, plumbing and mechanical drawings, and supportive data. | | elements. (4) When trusses are to be used, framing layouts and connection details are to be included. Truss design and | |
| | B. Plans must be drawn by a Nevada State Registered Architect or Engineer. The architect and/or engineer is responsible for the design and shall date, stamp, and sign each sheet submitted. Plans may also be drawn by a Nevada State Licensed Contractor or owner/builder when used for his own work. | | shop drawings prepared, stamped and signed by a Nevada licensed engineer must be submitted prior to permit issuance or deferred (if requested by applicant). Truss fabricator must be included in the current Clark County listing of approved truss fabricators. Truss calculations must be stamped by EOR prior to submittal as complying to the EOR design intent. | |
| 1.3 | STRUCTURAL PLANS AND DOCUMENTS, including but not limited to: | | E. General structural notes, material specifications, loading and structural design criteria are to be included | |
| | A. Submit two sets of structural calculations, specifications, soils report, and other documents as | | with the plans. | |
| | required. Each set of documents shall be stamped, signed | 1.4 | FLOOR PLANS: | |
| | and dated by the licensed engineer who has responsible charge of these documents. Three (3) sets of plans and calculations are to be submitted if Special Inspection is required. | | A. Names of rooms and spaces with complete dimensions. | |
| | | | B. Sizes and types of doors and windows. | |
| | B. When structural is submitted and Special Inspection is required, submit QAA-2 completed by | 1.5 | EXTERIOR ELEVATIONS: | |
| | engineer or if not required, provide engineer letter stating that Special Inspection is not required or indicate on plans. | | A. Wall coverings shall be specified by components, thickness, and material specification. | |
| | C. Foundation:□ (1) Foundation plan showing all footings, posts, | | B. One-coat stucco systems require an approved applicator. Owner/builders cannot apply these systems. | |
| | bearing walls, slabs, basement walls, stem walls, anchor bolts and spacing, hold-downs. | | C. Roofing shall be specified by its type, manufacturer's name, and the product name. | |

1.6

MISCELLANEOUS DETAILS:

| | A. | Construction features such as stairs, fireplaces, s, sunken tubs, etc. shall be detailed on the plans. | 1.9 | PLUMBING PLAN REQUIREMENTS: | |
|----------|---|--|--|--|--|
| □ 1.6 | B. access s | The location and size of readily accessible attic scuttles and attic ventilation shall be shown on the ith all necessary calculations. ELLANEOUS DETAILS: (continued) | | A. Location, size and material specification of all water and DVW piping to be shown on the plumbing floor plan. Fixture types to be indicated with appropriate symbols. Individual fixtures and fixture groups may have pipe sizes indicated in a fixture schedule. Provide water supply fixture unit count with required meter size. UPC | |
| | C. | Attic ventilation and calculations must be shown. | | Table 610.4 or Appendix L. | |
| | D. For room additions and remodeling of existing buildings, including mobile homes and manufactured buildings, provide plans and details of adjacent areas and | | B. Location and size of gas piping with Btu/h demands, pipe lengths and material used. | | |
| | connect informa | | | C. Location, type and size of water heater. Detail combustion air requirements if gas. | |
| | | When basements are installed, provide a cross all detail showing materials used, water proofing of | | D. Location and size of cleanouts to be shown. | |
| 1.5 | | side and egress window wells. | 1.10 | ADDITIONS OR ALTERATIONS TO PLUMBING/MECHANICAL: | |
| 1.7 | ELEC | TRICAL PLAN REQUIREMENTS: | | A Plan view of evicting mining to appliance/firstyness | |
| | A. provide | For additions or alterations to electrical systems, the following: | Ц | A. Plan view of existing piping to appliance/fixtures together with point of connection and new system. | |
| | ☐ (1) Plan of original structure showing areas being added or altered. | | B. BTU demand and distance of existing gas appliances to meter is required. | | |
| | oung u | | 1.11 | INTERNATIONAL ENERGY CONSERVATION | |
| | | (2) Size and location of existing and | | CODE: | |
| | proposed electrical service and sub-panels. Provide service and calculations to include the old and new loads. Load calculations not required if adding five (5) or less devices. | | A. Provide 2009 International Energy Conservation Code calculations. Include a completed Residential Energy Schedule applied to the plans. Window values should be | | |
| | | (3) Identify the names or uses of the new edrooms, porch, etc.). | | taken from manufacturer's NFRC label information. windows without NFRC labels, use the listed defavalues. (go to www.energycodes.gov – click on ResCheck | |
| | smoke d | (4) New outlets, switches, light fixtures, letectors, and special outlets. | | B. System Analysis: "Designed and stamped/signed by a State of Nevada licensed architect or engineer. | |
| 1.8 | MECH | IANICAL PLAN REQUIREMENTS: | | C. *Component performance | |
| | A. | Heating/Cooling unit capacity, location, and | | D. *Prescriptive requirements | |
| | working | g space for the following equipment: | | * No signature or stamp required | |
| | □ D | (1) Evaporative cooler Number of Horse | | | |
| | Power. □ | (2) Heat Pump tonnage and KW strip. | | | |
| | | (3) Electrical AC/furnace total KW demand. | | SEE ALSO: <u>SINGLE FAMILY DWELLINGS</u> | |
| | | (4) Gas furnace BTU demand or input. Note: and working space must be provided for all ed equipment. | | SUBMITTAL REQUIREMENTS ENERGY CODE REQUIREMENTS | |
| | B. □ | Type of duct work to be used. (1) Duct insulation information. | | | |
| | C. | Exhaust fans size, type, and location. | | | |
| | D. | Dryer vent location. | | | |
| | E. | Attic mounted/roof mounted equipment to show | Revise | Revised 11/11; 2/12; 2/15; 01/16 | |

method of support and engineering calculations if required. Access and a platform are to be detailed when a roof pitch

exceeds 4:12.

Revised 11/11; 2/12; 2/15; 01/16 ES: Residential Attached or Detached Structure Submittal Requirements